

B1
cont. has been proposed or ensuring such a minute connection pitch.--

IN THE CLAIMS:

Please amend Claims 1 and 13 to read as follows. A marked-up copy of Claims 1 and 13, showing the changes made thereto, is attached.

DS
Sub 4
B2

1. (Twice Amended) A circuit connection structure, comprising: a first substrate forming a display panel having electrode terminals formed thereon, a semiconductor device having first electrodes and second electrodes with the first electrodes directly connected to the electrode terminals of the first substrate, a flexible wiring member disposed in a lateral position with respect to the first substrate having thereon a pattern of conductors each extending from a first conductor end to a second conductor end on the flexible wiring member with the first conductor ends of the conductors connected to the second electrodes of the semiconductor device, and a circuit board disposed with a space from the first substrate and having thereon electrode terminals connected to the second conductor ends of the conductors on the flexible wiring member,

wherein said semiconductor device bridges the space between the first substrate and the circuit board.

Sub 2 DB
13. (Twice Amended) A display apparatus,

comprising:

a display panel comprising at least one substrate having thereon pixel electrodes extending to form electrode terminals on a peripheral side of the substrate,

a semiconductor device having input electrodes, and output electrodes for supplying drive waveforms to the pixel electrodes of the display panel, and

B³ a circuit board disposed with a space from the display panel and having electrode terminals for supplying an electric power and control signals to the semiconductor device; wherein

the electrode terminals on at least one substrate of the display panel are directly connected to the output electrodes of the semiconductor device, and

the semiconductor device is connected to the circuit board via a flexible wiring member disposed in a lateral position with respect to the substrate having thereon a pattern of conductors each extending from a first conductor end to a second conductor end so that the input electrodes of the semiconductor device are connected to the first conductor ends of the conductors on the flexible wiring member, and the second conductor ends of the conductors of the flexible wiring member